



Benefits:

- Special mount for Tamron MP3010
- Robust construction
- Compact size
- High IP protection class
- Flexible camera positioning
- High chemical resistance
- Vibration-proof mounting
- Excellent heat dissipation
- Installation of additional PCBs possible
- Lots of accessories available



Technische Details:

Inner Length	114mm
Dimensions (w x h x l, incl. cable gland)	66 x 66 x 148mm
Window Aperture	28mm
Window Material	BK7, double-sided anti reflection coating
Window Seal	Hytrel
Protection Class	IP66 (Nema 4) IP67 (Nema 6)
Order Number	100.010.602

Weight (without camera mount)	Approx. 800g
Enclosure Material	Anodized Aluminum
Enclosure Seals	NBR
Cable Gland Aperture	16.5mm
Cable Diameter	4-6.5mm
Cable Gland Seal	TPE



The mount guarantees excellent heat dissipation



Salamander S for Tamron MP3010 front and back view

Accessories:

Product	Image	Order No.	Product	Image	Order No..	Product	Image	Order No..
Air Nozzle		50.100.025	Mounting Kit 1		5.010.000	Mounting Kit 10		5.100.000
Pneumatic Shutter		50.200.010	Mounting Kit 2		5.020.000	Mounting Kit 15		5.150.000
Deflection Mirror 90°		20.020.004	Mounting Kit 6		5.060.000	Mounting Kit 16/16m		5.160.000 5.160.000m
El. Heating Plate		70.100.018	Mounting Kit 7		5.070.000	Mounting Kit 17/17m		5.170.000 5.170.000m
Sun roof Size S		20.010.001	Mounting Kit 9		5.090.000			

Further accessories as e.g. water cooling system on request.

Technical Drawing:

